



| Specification                | 16 Ohms | 32 Ohms | 150 Ohms |
|------------------------------|---------|---------|----------|
| W @ 1% THD                   | 0.2035  | 0.3719  | 0.3336   |
| Volts @ 1% THD               | 1.8046  | 3.4499  | 7.0738   |
| % THD+N 1kHz 0dBu            | 0.1116  | 0.0492  | 0.0217   |
| SMPT E IMD 0dBu              | 0.1062  | 0.0445  | 0.0214   |
| CCIF IMD 0dBu                | 0.0314  | 0.0141  | 0.0091   |
| DIM/TIM 0dBu                 | 0.0155  | 0.0260  | 0.0622   |
| Gain in dB (low)             |         | 13.6825 |          |
| Noise @ Low Gain in mVrms    |         | 0.1300  |          |
| Gain in dB (medium)          |         | 0.0000  |          |
| Noise @ Medium Gain in mVrms |         | 0.0000  |          |
| Gain in dB (high)            |         | 0.0000  |          |
| Noise @ High Gain in mVrms   |         | 0.0000  |          |
| Output Impedance             |         | 68.4168 |          |
| Channel Balance              |         | 0.5830  |          |



Left  
Right  
Left  
Right  
Left  
Right

0000

ght

)